K-43

MILLER ESTATES

BEING A PORTION OF SECTION 11 AND SECTION 10, T-13-S, R-6-E



LEGEND:
O= EXISTING IRON PINS
⊕ = CAPPED REBAR SET
R/W= RIGHT OF WAYS
P.O.C.=POINT OF COMMENCEMENT
P.O.B.=POINT OF BEGINNING

NOTE:
ALL LOTS MUST CONTAIN 3.0 AC.+-

GRAHAM PROPERTY
N.E.1/4-S.E.1/4
SECTION 10

ROBINSON 7.6/39

EXISTING AXLE
N 88°49'35" E
270.00'

EXISTING 1/4"REBAR
N 88°49'35" E
402.52'

N 88°49'35" E
642.46'

121.33'
N 04°35'10" W

N.W. CORNER
N.W.1/4-S.W.1/4
SECTION 11
T-13-S, R-6-E

BARRON
1471/133

N 04°35'10" W
202.48'

N 64°48'00" W
812.19'

N 35°04'45" W
614.68'

N 64°48'00" W
708.01'

N 64°48'00" W
551.39'

N 64°48'00" W
392.05'

N 04°35'10" W
1316.47'

N 04°35'10" W
1320.47'

N 04°35'10" W
1313.59'

S 04°35'10" E
1316.00'

S 04°35'10" E
402.48'

S 04°35'10" E
1320.00'

S 04°35'10" E
1320.47'

S 04°35'10" E
1316.47'

N 64°48'00" E
516.49'

S 25°14'00" E
36.71'

S 64°48'00" E
704.26'

N29°55'01"E 98.67'

S 75°43'19" E
971.85'

S 76°08'23" E
683.05'

S 64°48'00" E
537.16'

S 64°48'00" E
643.58'

S 64°48'00" E
629.90'

S 64°42'00" E
616.39'

S 64°42'00" E
1225.68'

S 64°42'00" E
476.32'

S 58°47'45" E
1109.42'

S 64°48'00" E
300.00'

S 25°11'09" W
411.97'

S 64°48'00" E
209.80'

S 64°48'00" E
209.80'

S 64°48'00" E
209.80